

2009



Standard roll over protection system is foldable to 90 degrees to allow cutting under low hanging limbs or parking in shallow areas.

Comfortable deep cushioned seats with retractable seat belts and foam padded steering levers with variable dampening are fully adjustable to suit the individual preference of any operator.


The control panel arrangement allows convenient access to controls and tilted fuel tank. The neck features an oversized opening for easy tie ups.

Convenient deck lift/height mechanism features standard foot assist and helper springs for reduced effort when raising and lowering the deck.

Molded rubber discharge shield yields to impacts and allows closer trimming without damage to the shield, trees or fences.




High performance HFS™ cutting deck features durable steel construction, reinforced front, side and spindle areas, heavy-duty anti-scalp roller mounts, Fusion™ blades and oversized cast iron blade hubs for increased durability.



Removable dimpled steel foot pan for easy access to deck belt pulleys, spindles and clean-up.

Caliper and disc style park brake gives positive holding power, even when transporting on trailers.



For commercial landscapers or large property owners, the Grizzly® ZTR® tames even the most demanding conditions. Rugged commercial construction along with premium engines, cutting decks and hydraulic drive systems combine to make the Grizzly® a powerful, durable performer.

**DIXON** ZTR®

## 2009 GRIZZLY Specifications

Model	Grizzly 52	Grizzly 60	Grizzly 60	Grizzly 72
<b>Part Number</b>	968999588	968999590	968999591	968999592
<b>Engine</b>	Kohler Command Pro Twin	Kohler Command Pro Twin	Kohler Command Pro Twin	Kohler Command Pro Twin
<b>Horsepower*</b>	27	27	30	30
<b>Starter</b>	Electric start	Electric start	Electric Start	Electric Start
<b>Hour Meter</b>	●	●	●	●
<b>Headlights</b>	●	●	●	●
<b>Cutting Width</b>	52"	60"	60"	72"
<b>Cutting Height</b>	Adjustable from 1.5" to 5.5"	Adjustable from 1.5" to 5.5"	Adjustable from 1.5" to 5.5"	Adjustable from 1.5" to 5.5"
<b>Anti-Scalp Rollers</b>	●	●	●	●
<b>Deck Construction</b>	HFS 11 gauge	HFS 11 gauge	HFS 11 gauge	HFS 11 gauge
<b>Spindle Type</b>	Cast iron	Cast iron	Cast iron	Cast iron
<b>Blades</b>	Fusion™	Fusion™	Fusion™	Fusion™
<b>Blade Engagement</b>	Electric clutch	Electric clutch	Electric clutch	Electric clutch
<b>Drive System</b>	10cc Parker with fan, TL Motor	10cc Parker with fan, TL Motor	10cc Parker with fan, TL Motor	10cc Parker with fan, TL Motor
<b>Controls</b>	Dual levers with foam padded hand grips	Dual levers with foam padded hand grips	Dual levers with foam padded hand grips	Dual levers with foam padded hand grips
<b>Speed</b>	10 mph	10 mph	10 mph	10 mph
<b>Front Caster Tires</b>	13 x 6.5 - 6	13 x 6.5 - 6	13 x 6.5 - 6	13 x 6.5 - 6
<b>Rear Tires</b>	23 x 9.5 - 13	24 x 12 - 12	24 x 12 - 12	24 x 12 - 12
<b>Seat Type</b>	Premium ballistic	Premium ballistic	Premium vinyl	Premium vinyl
<b>ROPS</b>	●	●	●	●
<b>Fuel Capacity</b>	9.5 Gallons	9.5 Gallons	9.5 Gallons	9.5 Gallons

● = Standard Equipment

\* All horsepower values are as rated by the engine manufacturer.

Continuous dedication to improve our products requires that specifications and designs are subject to change without notice.