

RAM ZTR

2009



- ▶ Durable ballistic cloth construction and extra deep seat cushions provide one of the most comfortable rides on the market.
- ▶ Comfortable foam padded steering levers, height adjustment control, park brake and fender mounted controls are all conveniently located within easy reach of the operator.
- ▶ Dual wide-angle headlights are standard equipment.



- ▶ Standard Fusion™ cutting blades stay sharp longer and are far more durable than ordinary blades.

TRANSMISSION OPTIONS



- ▶ **ZT2800**
The fully serviceable ZT2800 series transmissions feature 7" fans for uniform cooling, 1" diameter ball bearing supported axles, and guarded flters.



- ▶ **KANZAKI**
Kanzaki tandem pump and Parker wheel motors for smooth, durable performance. An oversized hydraulic reservoir provides better heat dissipation and longer component life.

DECK OPTIONS



- ▶ **TRI-FORCE**
The perfect balance of performance and durability. The extra deep welded steel cutting deck offers an exceptional cut quality, whether mulching, bagging or discharging.



- ▶ **TUNNEL FORCE**
Unique tunnel design provides exceptional performance in heavy mowing. Extra large discharge opening improves dispersal. Cast iron blade spindles compliment the solid welded steel construction.

The Ram series residential zero turn mower offers the perfect balance of value and performance. Comfortable padded seats, convenient control placement, premium high powered V-twin engines and rugged steel frames and decks combine to make it a favorite in the Dixon® lineup.

DIXON[®]ZTR[®]

2009 RAM SERIES Specifications

Model	RAM 48 ZT	RAM 50 ZT	RAM 50 KZ	RAM 50 KZ	RAM 61 KZ
Part Number	965882601	965882701	965882801	965882901	965883001
Engine	Kohler Courage Twin	Briggs & Stratton ELS Twin	Kohler Courage Twin	Kawasaki Twin	Briggs & Stratton ELS Twin
Horsepower*	24	26	24	21	26
Starter	Electric start	Electric start	Electric start	Electric start	Electric start
Hour Meter	Digital	Digital	Digital	Digital	Digital
Headlights	●	●	●	●	●
Cutting Width	48"	50"	50"	50"	61"
Cutting Height	Adjustable from 1.5" to 4" in 1/2" increments	Adjustable from 1.5" to 4" in 1/2" increments	Adjustable from 1.5" to 4" in 1/2" increments	Adjustable from 1.5" to 4" in 1/2" increments	Adjustable from 1.5" to 4" in 1/2" increments
Anti-Scalp Rollers	●	●	●	●	●
Deck Construction	Fabricated, Tri-Force™	Fabricated, Tunnel Force™	Fabricated, Tunnel Force™	Fabricated, Tunnel Force™	Fabricated, Tri-Force™
Spindle Type	Cast aluminum	Cast iron	Cast iron	Cast iron	Cast aluminum
Blades	Fusion™	Fusion™	Fusion™	Fusion™	Fusion™
Blade Engagement	Electric clutch	Electric clutch	Electric clutch	Electric clutch	Electric clutch
Drive System	ZT2800 with charge	ZT2800 with charge	Kanzaki / TE	Kanzaki / TE	Kanzaki / TE
Controls	Dual levers with foam padded hand grips	Dual levers with foam padded hand grips	Dual levers with foam padded hand grips	Dual levers with foam padded hand grips	Dual levers with foam padded hand grips
Speed	7 mph	7 mph	7.5 mph	7.5 mph	7.5 mph
Front Caster Tires	11 x 4.10 - 5	11 x 4.10 - 5	13 x 5 - 6 Bearing	13 x 5 - 6 Bearing	13 x 5 - 6 Bearing
Rear Tires	20 x 9.5 x 8	20 x 9.5 x 8	22 x 9.5 x 10	22 x 9.5 - 10	22 x 9.5 - 8
Seat Type	Deluxe ballistic with armrest	Deluxe ballistic with armrest	Deluxe ballistic with armrest	Deluxe ballistic with armrest	Deluxe ballistic with armrest
Seat Slides	●	●	●	●	●
Fuel Capacity	5 Gallons	5 Gallons	5 Gallons	5 Gallons	5 Gallons

● = Standard Equipment

* All horsepower values are as rated by the engine manufacturer.

Continuous dedication to improve our products requires that specifications and designs are subject to change without notice.